3300X Legendary Reliability

Avoids Hand Contact With Push Paddle Taps

- Manual taps and lack of any PCB's or solenoids makes for easy maintenance
- Built on the same platform, and uses many of the same parts as the well known, ArcticChill88/98 and ArcticStar55
- The 3300X fits our overflow kit, our cowlings and mains drainage kit with or without pump



Push The Glass Or Cup Against The Tap To Dispense



Robust & Reliable
The Epitome
Of Perseverance

3300X Legendary Reliability

Avoids Hand Contact With Push Paddle Taps

Accessories For The 3300X

Installation rail with filter. Includes compression fitting, 1-Micron green filter, water block, copper pressure reducing valve & non-return valve




Filter housing with carbon block candle & nanofilter



Cowling to fix the cooler securely to the wall. (Supplied separately)



Mains drainage - connect the drip tray to mains drainage. Can be supplied with a pump, to pump the water over 50m & a rise of 5m



10 litre overflow system with alarm to signal when full. (Factory fitted)



A pumped main drainage system pumps the waste water from the drip tray over a distance of 100m & a rise of 5m. (Factory installed)



3 Litre overflow kit connects the drip tray to a 3 litre alarmed overflow container. The container has a tap to empty without removing it



Description	Dimensions H x W x D mm	Weight
POU floor standing	1135 x 340 x 340	18
Bottled floor standing	1165 x 340 x 340	18
POU table top	460 x 340 x 340	15
Bottled table top	463 x 340 x 340	15